

Series Rechargeable sealed Lead-acid battery



MODEL	Voltage	Capaci ty	Resistan ce	Dimension (mm)				Weight (KG)
	(V)	(AH)	mΩ	(L)	(W)	(H)	(TH)	
6V								
SN-6V4CH	6	4	≤25	70	47	101	108	0.7
SN-6V7CH	6	7	≤15	151	34	94	103	1.4
SN-6V12C H	6	12	≤10	151	50	94	103	1.7
SN-6V100C H	6	100	≤5	195	170	207	232	15
SN-6V200C H	6	200	≤3	323	178	226	255	29
12V								
SN-12V4C H	12	4	≤40	90	70	102	108	1.4
SN-12V7C H	12	7	≤28	151	65	95	100	2.2
SN-12V12C H	12	12	≤20	152	99	95	104	4.0
SN-12V17C H	12	17	≤16	180	76	168	168	5.5
SN-12V24C H	12	24	≤11	165	126	175	182	8.0
SN-12V38C H	12	38	≤8.5	197	166	175	182	12.6
SN-12V55C H	12	55	≤8	230	138	210	215	16.5
SN-12V65C H	12	65	≤6	350	166	179	183	20.5
SN-12V100 CH	12	100	≤4.4	329	172	214	238	30.0
SN-12V120 CH	12	120	≤4.0	408	174	208	237	35.0
SN-12V150 CH	12	150	≤3.5	482	170	240	240	43.0
SN-12V200 CH	12	200	≤3	522	240	219	244	61.0
Note: A. The rate capacity (10 rate hour) is the average tested by several times at 25°C. B. The total height of battery includes the terminal.								